



No Lesen : PC001393

Licence No :

LESEN PENSIJILAN BARANGAN

Product Certification Licence



SIRIM

SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada
SIRIM QAS International Sdn. Bhd. hereby grants to

**PGF INSULATION SDN. BHD.
NO. 2449, LORONG PERUSAHAAN 10
PRAI INDUSTRIAL ESTATE
13600 PRAI
PULAU PINANG, MALAYSIA**

**Lesen untuk menggunakan Tanda Pensijilan di atas barangan
a licence to use the Certification Mark on
INSULATION MATERIALS (MINERAL WOOL)**

Please refer to detail in the SCHEDULE

**sebagai mematuhi keperluan
*as complying with***

MS 1020 : 2010

BS 476 : PART 6 : 1989 + A1 : 2009

BS 476 : PART 7 : 1997



Mohd Azanuddin bin Salleh
Pengarah Urusan
Managing Director
SIRIM QAS International Sdn. Bhd.

SIRIM QAS International Sdn. Bhd.
(No. Syarikat 410334-X)
1, Persiaran Dato' Menteri
Seksyen 2, Peti Surat 7035
40700 Shah Alam
Selangor Darul Ehsan
MALAYSIA.

Tel : 60-3-55446400
Faks : 60-3-55446466

<http://www.sirim.my>
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 26 September 2014

Certified Since

Sah Sehingga : 26 September 2018

Valid Until

Tarikh Dikeluarkan : 22 August 2017

Issue Date

No Siri : 032899

Serial No

Lesen Ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.

This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.

SCHEDULE

PGF INSULATION SDN. BHD.



Brand : ECOWOOL
Model : ECOWOOL CLASSIC; Board
Rating : Density range: (24-90) kg/m³
Fire Propagation Index: 5.5, 7.9, 8.4, 8.8
Surface Spread of Flame: Class One
Fire Classification: CLASS O

Type : Glasswool
Size : Width range: (0.595 - 1.2) m
Length range: (0.595 - 2.3) m
Thickness range: (13 - 50) mm

Brand : ECOWOOL
Model : ECOWOOL CLASSIC; Roll
Rating : Density range: (9.5 - 48) kg/m³
Fire Propagation Index: 6.5, 1.8, 0.8, 4.0, 2.8, 8.1
Surface Spread of Flame: Class One
Fire Classification: CLASS O

Type : Glasswool
Size : Width: 1.2 m
Length range: (7.5 - 30) m

Thickness range:
1. (9.5 - 48) kg/m³: 50 mm
2. (14 - 48) kg/m³: (25 - 50) mm

End of page
